



KICK STAND KS-35



PRODUCT DESCRIPTION

Product Description and Application

A bicycle double leg kick stand, especially designed for a comfortable and stable stand of city-, trekking- and hybrid bicycles which are equipped with central kick stand plate with 9.5 mm hole diameter (at least).

FEATURES

- With a strong spring, to assure a stable parking condition by the kick stand
- Adjustable in leg length for a flexible use on various bicycles from 24" up to 28" wheel size
- With two black PP stand stops for "all terrain" use
- The 195 mm foot width creates stable parking condition for the bicycle to avoid a toppling bike

TECHNICAL INFORMATION

Kick stand

- Extruded aluminium, Al-6061 (-T6/-T4), matt silver anodized or electro dyed black
- Stand stops made of black polypropylene and coming with red polypropylene press buttons
- 14 index notches in both kick stand legs allows an adjustment for use on 24" up to 28" wheel bikes

Fastener

- 1 x 3/8" silver coated (UCP) steel screw with 8 mm hexagon socket for Allen key use
- 1 x silver coated (UCP) steel spring washer

Dimensions:

- Minimum length -24": approx. 295 mm (from plate to each stand stop)
- Maximum length -28": approx. 372 mm (from plate to each stand stop)

Weight:

500 g

INSTALLATION**Installation & Maintenance**

- For instructions how to mount this kick stand please check the [kick stand assembly-instructions](#)
- Clean and lubricate the link and spring in case of any difficulties by folding the kick stand