



PEDAL SP-2828

PRODUCT DESCRIPTION

Product Description and Application

A bicycle pedal with an extra-large “non-slip” tread areas at both sides and a sturdy aluminium centre body, specially designed to be use on e-bikes. Can also be used for city, trekking and hybrid bikes.

FEATURES

- The “Cartridge Bushing” bearing system guaranties a frictionless movement
- The pedals come with integrated and approved retro-reflectors on both sides and a sealed bearing system

TECHNICAL INFORMATION

Pedal type

“3 Component Pedal” comes with:

- Aluminium body, die cast, shiny ball polished or electro dyed (ED) black
- Cage made from black Polypropylene
- Extra-large tread surfaces made with a TPE (Thermo-Plastic-Elastomer) “non slip” in grey.

Bearing

- Maintenance free “industry standard” bearing systems on both sides
- Each pedal is equipped with one cartridge bearing and one slide bushing

Axle

- CrMo-steel, heat treated to 75HRA (+/-3) case hardness
- With 9/16” x 20TPI threading

Retro Reflectors

- Integrated in cage
- Approved (BS, JIS, TPP) and in accordance with German StVZO regulations

Dimensions

- 111* x 90 x 27 mm (*Length x Width x Height)
**Length = maximum pedal length while mounted (protruding out of the crank)*

Weight

504 g/pair

Standards

The pedal is certificated to meet the ISO standard

ISO 4210-8: "Cycles – Safety requirements for bicycles-Pedals and drive system test methods"

INSTALLATION

Installation & Maintenance

- For assembly and disassembly of your pedal please check the [pedal assembly instructions](#)
- Check your pedal conditions before every ride
- Change your pedals when the tread areas wear out

OPTIONS

- This pedal is also available with a lightweight cone ball bearing system.
Check [SP-828](#) for more information.
- A similar pedal is available as "2 Component Pedal", with a one-piece black Polypropylene cage and centre body.
Check [SP-827](#) for more information.