



PEDAL SP-600



PRODUCT DESCRIPTION

Product Description and Application

A bicycle pedal with a die cast aluminium body, specially designed to use on trekking and mountain bikes.

FEATURES

- The new “light weight” ball bearing system gives substantial weight and height reductions
- The pedals come with attached and approved retro-reflectors on both sides and a sealed bearing system

TECHNICAL INFORMATION

Pedal type

“Aluminium Pedal” comes with:

- Aluminium body, die cast, sand blasted and ED-black coated
- CNC machined silver finish.

Bearing

- Adjustable and light weight cone ball bearing system, on both sides
- With 14 x 3/32” bearing balls each side

Axle

- Boron-steel, heat treated to 75HRA (+/-3) case hardness

- With 9/16" x 20TPI threading

Retro Reflectors

- "Snap on" reflectors on both sides
- Approved (BS, JIS, TPP) and according German StVZO regulations (K369)

Dimensions

102* x 78 x 23 mm (*Length x Width x Height)

**Length = maximum pedal length while mounted (protruding out of the crank)*

Weight

272 g/pair

Standards

The pedal is designed and produced according to the EN standard
EN-14766 "Mountain-Bicycles - Safety requirements and test methods"

INSTALLATION

Installation & Maintenance

- For assembly and disassembly of your pedal please check the [pedal assembly instructions](#)
- Check your pedal conditions before every ride
- Adjustment and lubrication of the ball bearings is possible

OPTIONS

This pedal is also available with a high-end CrMo axle and lightweight sealed cartridge system. Check [SP-2600](#) for more information.